

Hampton Mfg., Inc. Makers of H-42 Products
135 Bethea Road Suite 501 Fayetteville, GA 30214 .770.461.0220 .800.451.5417
Fax 770.461.3290

MATERIAL SAFETY DATA SHEET
(Complies with hazard Communication Standard 29 CFR 1910.1200)

SECTION I - PRODUCT IDENTIFICATION

Product Name: H-42 Styling Iron Cleaner
Sales Name: H-42 Styling Iron Cleaner
DOT Shipping Name: N/A
DOT Hazard Class: N/A
Emergency Assistance: Call CHEMTREC 1.800.424.9300

SECTION II - HAZARDOUS INGREDIENTS

MATERIAL	CAS NO.	WT%	HAZARD	PEL	TLV
2-Butoxyethanol	111-76-2			50	25

SECTION III - PHYSICAL DATA

Boiling Point:	100 degrees
Vapor Pressure:	N/A
Vapor Density:	N/A
Specific Gravity @ 25 C	1.100
Solubility In Water:	Complete
pH:	12.6
Appearance:	Pale Yellow Liquid
Odor:	Lemon

SECTION IV – FIRE AND EXPLOSION INFORMATION

FLASH POINT (TCC) None to boiling .
EXPLOSIVE LIMIT N/A
EXTINGUISHING MEDIA: Dry chemical, water fog, regular foam, and carbon dioxide.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion will produce carbon di-oxide, possibly carbon monoxide, and nitrogen compounds.

FIREFIGHTING PROCEDURES: Wear full protective clothing and self-contained positive pressure breathing apparatus with full face shield.

SPECIAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by open flames or heat. Never use welding or cutting torch on or near drum (even empty).

Hampton Mfg., Inc. Makers of H-42 Products
135 Bethea Road Suite 501 Fayetteville, GA 30214 770.461.0220 800.451.5417
Fax 770.461.3290

SECTION V - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL: Not established for product.

EFFECTS OF ACUTE OVEREXPOSURE

Eyes: Can cause irritation.

Skin: Can cause irritation and dermatitis with prolonged contact.

Inhalation: Can cause nausea and headaches.

Ingestion: Can cause vomiting and nausea, possibly producing a toxic effect on red blood cells based on animal data only.

FIRST AID

In Eyes: Immediately flush with large amounts of water for at least 15 minutes while forcibly holding eyelid apart to ensure complete irrigation of all eye and lid tissue. Get Medical attention. On Skin: Thoroughly wash exposed area with lots of soap and water. Remove contaminated clothing and shoes; wash before reuse. Get medical attention if irritation persist after washing.

If Inhaled: Move individual to fresh air. If there are any symptoms of overexposure, get medical attention.

If Ingested: Immediately drink two large glasses of water. Get medical attention. Do not give anything by mouth to an unconscious or convulsing person. Get medical attention immediately.

PRIMARY ROUTE(S) OF ENTRY: Inhalation, skin contact.

SECTION VI- REACTIVITY DATA

HAZARDOUS POLYMERIZATION: None

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizing agents.

SECTION VII - SPILL OR LEAK PROCEDURES

Eliminate sources of ignition. Absorb with earth, sand, floor absorbent or similar inert material. If large spill, dike area to prevent spreading. Dispose of waste in accordance with federal, state and local regulations. Flush spill area with water.

Hampton Mfg., Inc. Makers of H-42 Products
135 Bethea Road .Suite 501 Fayetteville, GA 30214 .770.461.0220 .800.451.5417
Fax 770.461.3290

SECTION VIII

Avoid contact with eyes and skin. Wear eye protection, and solvent resistant gloves. Contact lenses should not be worn when working with chemicals; they may contribute to the severity of eye injuries. Wash thoroughly after handling. Avoid confined work areas, use with adequate ventilation. Keep container away from heat and flame.

SECTION IX - PRECAUTIONS OR OTHER COMMENTS

Do not cut, grind, weld, or drill on or near this container. Empty containers will retain residues and should be treated as if they were full.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not, recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.